



## YOSHIDA AIR TOOLS



**YA-5K-2** - 120° Power Brush/Grinder

| Specifications                             |          |
|--|----------|
| Model                                      | YA-5K-2  |
| Throttle type                              | Roll     |
| Rotational Frequency (min-1)               | 8,400    |
| Sanding Paper Size(mm)                     | 125x16   |
| Overall length (mm)                        | 233(200) |
| Head Height (mm)                           | 81.5     |
| Net weight (kg)                            | 1.5      |
| Max Air Consumption (Nm <sup>3</sup> /min) | 0.95     |
| Air Hose size (mm)                         | 12.7     |
| Air Inlet Thread                           | RC3/8    |



**YGT-6** - Mini Palm Grinder

| Specifications                             |        |
|--|--------|
| Model                                      | YGT-6  |
| Throttle type                              | Lever  |
| Exhaust Direction                          | Front  |
| Rotational Frequency (min-1)               | 20,000 |
| Collet size (mm)                           | 6      |
| Overall Length (mm)                        | 76.0   |
| Net weight (kg)                            | 0.4    |
| Max Air Consumption (Nm <sup>3</sup> /min) | 0.25   |
| Air Hose size (mm)                         | 9.5    |
| Air Inlet Thread                           | RC1/4  |

## NKC QUICK COUPLERS (stainless steel option)

Made in Japan

### Socket

| Std Code | Hose Size(in) | SH (Hose Nipple) |
|----------|---------------|------------------|
| 22SH     | ¼             |                  |
| 23SH     | SS ⅜          |                  |
| 24SH     | SS ½          |                  |
| 44SH     | ½             |                  |
| 46SH     | ¾             |                  |

| Std Code | Thread Size (in) | SM (Male Thread) |
|----------|------------------|------------------|
| 22SM     | ¼                |                  |
| 23SM     | ⅜                |                  |
| 24SM     | SS ½             |                  |
| 44SM     | ½                |                  |

| Std Code | Thread Size (in) | SF (Female Thread) |
|----------|------------------|--------------------|
| 22SF     | ¼                |                    |
| 23SF     | ⅜                |                    |
| 24SF     | ½                |                    |

SS: Stainless steel option

### PLUG

| Std Code | Hose Size(in) | PH (Hose Nipple) |
|----------|---------------|------------------|
| 22PH     | ¼             |                  |
| 23PH     | ⅜             |                  |
| 24PH     | ½             |                  |
| 44PH     | ½             |                  |
| 46PH     | ¾             |                  |

| Std Code | Thread Size (in) | PM (Male Thread) |
|----------|------------------|------------------|
| 22PM     | ¼                |                  |
| 23PM     | ⅜                |                  |
| 24PM     | ½                |                  |
| 44PM     | ½                |                  |

| Std Code | Thread Size (in) | PF (Female Thread) |
|----------|------------------|--------------------|
| 22PF     | ¼                |                    |
| 23PF     | ⅜                |                    |
| 24PF     | ½                |                    |



**NL-P-2**  
One to Two Line Connector