

TPB SERIES - Concrete Breaker



TPB-30 - 15.0kg

TPB-40 - 18.0kg

TPB-60 - 30.0kg
TPB-73 - 31.0kg
TPB-90 - 42.0kg

Muffler - Optional for all breakers

- Forged steel body for maximum durability
- 4-Bolt head design - rugged handling
- Latch Retainer - quick chisel changing

Optional Accessories for TCD-30, TPB-30, TPB-40 (for more accessories please see Pg. 60)

Model	Description	OA Length (mm)	Shank Size 1"Hex x 4/4"	Model	Description	OA Length (mm)	Shank Size 1"Hex x 4/4"
M4	Moil Point	580		D4	Digger 3"	500	
M4L	Long Moil Point	1330		DW4	Digger 5"	490	
C4S	Chisel	500		A4	Asphalt Cutter	505	

Optional Accessories for TPB-60, TPB-73, TPB-90 (for more accessories please see Pg. 60)

Model	Description	OA Length (mm)	Shank Size 1 1/4"Hex x 6 1/4"	Model	Description	OA Length (mm)	Shank Size 1 1/4"Hex x 6 1/4"
M1S	Moil Point	550		DW1	Digger 5"	545	
M1	Moil Point	620		A1	Asphalt Cutter	540	
M1L	Moil Point	760					
C1	Chisel	610					
D1	Digger 3"	570					

Specifications: Air Pressure 6kg/cm²

Model	Piston Diameter (mm)	Piston Stroke (mm)	Blow Per Min (bpm)	Net Weight (kg)	Overall Length (mm)	Avg. Air Cons.		Air Inlet (pt)	Hose Size (mm)	Shank Size
						(m ³ /min)	(cfm)			
TPB-30	44.45	85	1,550	15	564	1.4	49.4	1/2	12.7	1"Hex x 4 1/4"
TPB-40	44.00	146	1,100	18	660	1.6	56.5	3/4	19.0	1"Hex x 4 1/4"
TPB-60	57.15	100	1,400	30	645	2.0	70.6	3/4	19.0	1 1/4"Hex x 6"
TPB-73	57.15	144	1,200	31	690	1.8	63.6	3/4	19.0	1 1/4"Hex x 6"
TPB-90	66.67	152	1,250	42	723	2.2	77.7	3/4	19.0	1 1/4"Hex x 6"