

ROCK DRILL- Hand Held (5.8kg)

Mini Concrete and Rock Drill



TH-5S - 5.8kg



Insert Bit (TH-5S)

Insert Bit - Diameter x Length
13mm x 250mm
13mm x 400mm
16mm x 400mm
16mm x 600mm
19mm x 400mm
19mm x 600mm
22mm x 280mm
22mm x 400mm
22mm x 600mm



Taper Rod

Drill Bit

Taper Rod T-19 (OAL)	Carr Bit T-19 (Dia)	Taper Rod T-15 (OAL)	Carr Bit T-15 (Dia)
400mm	24mm	400mm	20mm
600mm	26mm	600mm	22mm
900mm	28mm	900mm	
1,200mm	30mm		
	32mm		
	34mm		
	36mm		
	38mm		

ROCK DRILL - Hand Held (14kg - 27kg)



TJ-15LBS - 14.0kg



TJ-20LBS - 18.5kg



TS-55 - 27.0kg

Optional Muffler



TJ-15
TJ-20

Specifications: Air Pressure 6kg/cm²

Model	Piston Diameter (mm)	Piston Stroke (mm)	Blow Per Min (bpm)	Rotary Speed (rpm)	Net Weight (kg)	Overall Length (mm)	Avg. Air Cons. (m ³ /min)	Hose Size (mm)
TH-5S	38.0	35	3,400	420	5.8	425	0.85	12.7
TJ-15LBS	54.0	45	2,450	250	14.0	507	1.60	19.0
TJ-20LBS	68.0	49	2,400	200	18.5	610	2.50	19.0
TS-55	66.6	65	1,800	200	27.0	568	2.60	19.0


T-22 Taper Rod and Drill Bit



Button Bit:
Higher drilling speed suitable for all kinds of rock or sand formation. Re-sharpening of bit is not necessary



Carr Bit:
Suitable for rock formation without cracks



Drill Bit

Taper Rod

Button Bit T-22 (Dia)
28mm
30mm
32mm
34mm
36mm
38mm
40mm
42mm
45mm

Button Bit T-22 (Dia)
48mm
50mm
55mm

Carr Bit T-22 (Dia)
36mm
44mm
46mm

Taper Rod T-22 (OAL)
600mm
900mm
1,200mm
1,500mm
2,400mm
3,000mm
4,000mm

Other sizes available on request