

## PEENING PREPARATION TOOLS - Handheld Scarifiers

The PPT range of hand scarifiers utilise the 3M™ brand of Rotopeen™ 'C' flaps to offer a captive shot method of surface preparation. Used with the range of Trelawny TVS dust collectors, the PPT will remove hazardous materials such as lead based paints and contaminated particles rapidly and dust free.

### Applications

A range of steel and concrete substrates can be cleaned and prepared to provide a keyed surface using these high production tools.

### Ideal for the removal of:

- Alkyds
- Mastics
- Epoxies
- Adhesives
- Lead based paints
- Coatings corrosion
- Abatement projects



Pneumatic model 194.C405  
100mm cutting width with star  
cutters



Pneumatic model 194.0405  
100mm cutting width with "C" Flaps



Electric options available : 220v/110v 1ph 50 Hz

Part No.	Cutting Width		Cutting Media		Power	Weight (kg)	RPM	Air Cons. (m³/min)	Vibration level Aeq (m/s²)
	50mm	100mm	'C' Flaps	Star Cutters					
194.0405		√	√		Air	4.10	2,700	0.85	3.10
194.C405		√		√	Air	6.47	2,700	0.85	4.60

## Accessories

HEAVY  
SCALING



Star cutter

Aggressive removal of thick  
coatings  
Part No. 312.S200



Beam cutter

Removal of hard coatings, less  
aggressive than star  
Part No. 312.R200



3M™ Heavy Duty Rotopeen™  
'C' Type Flap

Removal of light paint and rust to  
a bare metal finish  
Part No. 312.MRPC

LIGHT  
BURNISHING



### Air/Electric Vacuum System

Series K is ATEX approved for Gas Zone 1 & Dust  
Zone 21 under Category 2 of the ATEX Directive.