

CABLE REEL WITH LAMP



5907/328



5907/329



5907/370



5908/308

Model	Description	Metres of Coiled Cable	Max Watt bulb	Lamp Protection Degree	Weight (kg)	Reel protection Degree
5907/328 230 V	Cable reel with fluo lamp 328 230 Volt	14 + 1.5	11	IP 55	4.5	IP 42
5907/329 230 V	Cable reel with LED lamp 329 230 Volt	14 + 1.5	30 Led	IP 55	4.5	IP 42
5907/370	Cable Reel with lamp 370	14 + 1.5	60	IP 65	4.5	IP 42
5908/308 24V	Cable reel with Transfo + Fluo Lamp 308 24Volt	14 + 1.5	11	IP 55	4.5	IP 42

RETRACTABLE CABLE REEL



4315



5822/XF
 5825/XF
 5834/XF
 5838/XF



7315
 7325
 7525RNF

Model	No. of Conductor	Voltage (V)	Amperage (A)	Conductors section (mm ²)	Weight (kg)	Meters of Coiled Cable
4315	3	230/110	16	1.5	5.0	14 + 1
5822/XF	4	400	20	2.5	4.0	5.5 + 1.5
5825/XF	3	230/110	25	2.5	4.0	7 + 1.5
5834/XF	1	-	43	6.0	4.0	12.5 + 1.5
5838/XF	8	-	10	1.0	4.0	5.5 + 1.5
7315	3	230/110	16	1.5	10.0	25 + 2
7325	3	230/110	25	2.5	10.0	20 + 2
7525RNF	5	400	20	2.5	10.0	10 + 2