

QUICK COUPLERS

Why Jopla plastic couplers are better?

1. **Weight** is about 1/3 of metal type - greatly reduce operator's tiredness
2. **NO RUST** - Corrosion resistant
3. **Easy Operation** - One touch - connect & disconnect
4. **Impact resistant** - strong as metal couplers. Very high durability plastic material used.
5. Can be used on other Japanese metal couplers.
6. **Maximum Air Flow** - Valve design system
7. Plastic prevent sparks in flammable atmosphere

Jopla couplers are about 1/3 the weight of metal couplers lighter weight will reduce operator's tiredness and increase productivity.

Once touch - Jopla couplers coupled and uncoupled easily - higher productivity



Metal coupler

Jopla coupler
Lighter & better

Part No.	I.D.	O.D.	Part No.	I.D.	O.D.
TN-5NR	5mm	8mm	JN-5N	5mm	8mm
TN-6.5NR	6.5mm	10mm	JN-6.5N	6.5mm	10mm
TN-8N	8mm	12mm	JN-8N	8mm	12mm
TN-8.5N	8.5mm	12.5mm	JN-8.5N	8.5mm	12.5mm
TN-9N	9mm	15mm	JN-9N	9mm	15mm
Socket - TN Tube Connection			Plug - JN Tube Connection		

Part No.	Size	Part No.	Size
TS-2NR	1/4"	JS-02	1/4"
TS-3NR	3/8"	JS-03	3/8"
TS-4NR	1/2"	JS-04	1/2"
Socket - TS Male Thread		Plug - JS Male Thread	

TT-2NR	1/4"	JT-02	1/4"
TT-3NR	3/8"	JT-03	3/8"
TT-4NR	1/2"	JT-04	1/2"
Socket - TT Hose End		Plug - JT Hose End	

TL-1NR	1/4"	JF-02	1/4"
One to two socket connector (Twin socket)		Plug - JF Female Thread	

Part No.	Size	Part No.	Size
JSL-02	1/4"	JTL-02	1/4"
JSL-03	3/8"	JTL-03	3/8"
JSL-04	1/2"	JTL-04	1/2"
Elbow Plug - JSL Male Thread		Elbow Plug - JTL Hose End	

JOPLASTAR AIR DUSTER & ACCESSORIES

TD-30HN - JoplaStar Air Duster is suitable for many applications such as blow drying, cooling and cleaning by air flow.

Reasons why we choose JoplaStar

- Full Trigger reduces operator's fingers fatigue
- Flow controller knob
- Complete with 140mm nozzle

