

YOSHIDA AIR TOOLS



YA-4C-12F - Angle Grinder (Safety Lever)



YGT-6 - Mini Palm Grinder



YA-5K-20 - 120° Power Brush/Grinder (Roll Throttle)



YA-5K-2F - 120° Power Brush/Grinder (Safety Lever)

Model	Type	RPM	Wheel Size (mm)	OAL (mm)	Height (mm)	Weight (kg)	Max. Air Cons(m3/min)	Hose Size (mm)	Air Inlet (in)
YA-4C-12F	Lever	12,500	100 x 6 x 16	246	77.0	2.01	0.68	9.5	3/8
YA-5K-20	Roll	8,400	125 x 16	233 (200)	81.5	1.50	0.95	12.7	3/8
YA-5K-2F	Lever	8,400	125 x 16	261 (227)	81.5	1.63	0.95	12.7	3/8
YGT-6	Lever	20,000	-	76	-	0.40	0.25	9.5	1/4

NKC QUICK COUPLERS (stainless steel option)

Made in Japan

Socket

Std Code	Hose Size(in)	SH (Hose Nipple)
22SH	¼	
23SH	SS ⅜	
24SH	SS ½	
44SH	½	
46SH	¾	

Std Code	Thread Size (in)	SM (Male Thread)
22SM	¼	
23SM	⅜	
24SM	SS ½	
44SM	½	

Std Code	Thread Size (in)	SF (Female Thread)
22SF	¼	
23SF	⅜	
24SF	½	

SS: Stainless steel option

PLUG

Std Code	Hose Size(in)	PH (Hose Nipple)
22PH	¼	
23PH	⅜	
24PH	½	
44PH	½	
46PH	¾	

Std Code	Thread Size (in)	PM (Male Thread)
22PM	¼	
23PM	⅜	
24PM	½	
44PM	½	

Std Code	Thread Size (in)	PF (Female Thread)
22PF	¼	
23PF	⅜	
24PF	½	



NL-P-2
One to Two Line Connector