

## POLY-PTX® 800 Basic Machine (5801A)

Specification	
Grinding Speed (rpm)	1,000-3,500
Motor (Watt)	1,750
Voltage	230V, 50/60Hz
Grinding Width (mm)	100
Weight (kg)	3.3



Completes with ECO adaptor and Fleece wheel Grit 80.



Quintuple Swiveling handle for right and left handers. Vibration Reduction Handle for fatigue-free work.



Rubberised handle for optimum and anti-slip handling.



Convenient Speed regulation during operation with speedometer generator for constant speed under load.



QUICK-LOCK Cable quick connection for fast convenient change.



Dustproof field coil through special coating

## VARILEX® WSF 1800 Professional (5802)



### Features:

- Ideal for grinding and polishing application
- Can be used with flap discs, grinding and cutting discs
- Simple and fast changing of discs
- Variable speed control

Specification	
Grinding Speed (rpm)	2,000 - 7,600
Wheel Diameter (mm)	Ø115 - 180
Thread	M14
Motor (watt)	1,750
Voltage	230V 50/60Hz
Weight (kg)	2.8

## PIPE-MAX 802 HT (5803A)



### Features:

- Perfect grinding and polishing on closed and open pipes
- Fast, easy belt changing
- Homogenous and uniform grinding
- Adjustable Handle for both right or left handed operator

Specification	
Grinding Speed (rpm)	820-3,000
Motor (watt)	1,750
Voltage	230V 50/60Hz
Weight (kg)	4.8
Belt Dimensions (mm)	40 x 780



Special Zirconium Belt



SC Fleece Belt

### Accessories

Special Zirconium Belt	For grinding spot welds, eliminates deep scratches and rust - G40/60/80/120
SC Fleece Belt	For removing minor scratches & oxide layers to produce matt and satin finish - Coarse G80, Medium G180, Fine G280, Superfine G400