

# IMPACT WRENCH

## 3/4" to 1 1/2" square drive



**MI-2500GL - 3/4" & 1"**  
**MI-3800GL - 1"**

- Pin-less clutch mechanism
- 2-step throttle for precise control
- Elastomer side handle grip
- 4-Position regulator
- Available in 3/4" and 1"



**MI-5000GL - 1"**

- Pin-less clutch mechanism
- 2-step throttle for precise control
- Elastomer side handle grip
- 4-Position regulator



**MI-38GL - 1"**  
**MI-42GL - 1"**

- Twin-hammer clutch mechanism
- 2-step throttle for precise control
- Elastomer side handle grip
- 4-Position regulator



**MI-5500 - 1 1/2"**

- Pin-clutch mechanism
- Powerful for extra heavy duty work



Specifications: Air Pressure 6kg/cm<sup>2</sup>

Torque: 1.0kg.m = 9.807Nm = 7.233ft.lb

Model	Square Drive (in)	Bolt Size (mm)	Torque Range (kg.m)	Max Torque (kg.m)	Net Weight (kg)	Overall Length (mm)	Free Speed (rpm)	Avg. Air Cons (m <sup>3</sup> /min)	Air Inlet (pt)	Hose Size (in)	Shank Size - L (mm)
MI-2500GS	3/4	25	50-110	130	8.2	341	5,300	0.7	3/8	1/2	-
MI-2500GL	3/4	25	50-110	130	9.3	459	5,300	0.7	3/8	1/2	150
MI-2500GS	1	25	50-110	130	8.5	341	5,300	0.7	3/8	1/2	-
MI-2500GL	1	25	50-110	130	8.2	341	5,300	0.7	3/8	1/2	150
MI-3800GS	1	38	50-150	200	9.5	335	4,700	1.0	1/2	1/2	-
MI-3800GL	1	38	50-150	200	10.2	504	4,700	1.0	1/2	1/2	200
MI-38GL	1	38	50-110	180	7.9	498	3,700	0.7	1/2	1/2	200
MI-42GS	1	42	50-180	260	10.2	370	3,900	1.0	1/2	1/2	-
MI-42GL	1	42	50-180	260	10.6	519	3,900	1.0	1/2	1/2	200
MI-5000GS	1	50	50-220	270	14.3	460	3,700	1.0	1/2	1/2	-
MI-5000GL	1	50	50-220	270	16.0	594	3,700	1.0	1/2	1/2	230
MI-5500	1 1/2	55	150-428	560	18.1	520	2,800	0.9	1/2	1/2	-