

## LIGHT & HANDY DIE GRINDER

## General Maintenance



**MG-7206B** - rear exhaust



**MG-7236B** - front exhaust



**MG-7204B** - front exhaust



**MG-20** - front exhaust

### Recommended



SE-140 End Brush  
 Ø 16mm  
 (Made in Japan)

- Safety Lever Throttle
- High Speed, low vibration
- Compact, light and handy
- Ideal for grinding and deburring
- 6mm Collet (Standard)
- Optional ¼" or 3mm collect on request

Specifications: Air Pressure 6kg/cm<sup>2</sup>

Model	Collet Size (mm)	Wheel Size (mm)	Net Weight (kg)	OA Length (mm)	Free Speed (rpm)	Avg. Air Cons (m <sup>3</sup> /min)	Air Inlet (pt)	Hose Size (in)
<b>MG-7206B</b>	6 (3 & ¼" Optional)	25	0.6	146	22,000	0.5	¼	¾
<b>MG-20</b>	6 (3 & ¼" Optional)	25	0.6	139	22,000	0.6	¼	¾
<b>MG-7236B</b>	6 (3 & ¼" Optional)	25	0.4	123	18,000	0.38	¼	¾
<b>MG-7204B</b>	6 (3 & ¼" Optional)	25	0.4	120	25,000	0.38	¼	¾

## DIE GRINDER & STRAIGHT GRINDER

## Industrial Duty

Straight grinders are Industrial Heavy Duty for general Grinding, Sanding and Wire Brushing Applications.



**TG-25ZII** - 6mm Collet Die Grinder



**TG-38Z** - 6mm Collet Die Grinder



**TG-38ZL** - Lever Type

\*Lever Type (L) Grinders are available upon request.



**TSG-3F** - 3" Straight Grinder  
**TSG-3L** - Lever Type



**TSG-3C** - 6mm Collet Die Grinder  
**TSG-3CL** - Lever Type

For more options on the Carbide Burrs, please refer to page 43 on **procut** Carbide Burrs



For more options on the wire brushes, please refer to Page 45 and 46 on Industrial Wire Brushes.



**TSG-5S** - 5" Straight Grinder/Wire Brushing  
**TSG-5L** - Lever Type



**TSG-6S** - 6" Straight Grinder/Wire Brushing  
**TSG-6L** - Lever Type

Specifications: Air Pressure 6kg/cm<sup>2</sup>

Model	Wheel Size (mm)	Collet Size (mm)	Max Cut Speed (m/min)	Net Weight (kg)	Overall Length (mm)	Free Speed (rpm)	Avg. Air Cons (m <sup>3</sup> /min)	Air Inlet (pt)	Hose Size (in)	Power (HP)
<b>TG-25ZII</b>	25	6	-	0.56	150	18,000	0.50	¼	¾	0.4
<b>TG-38Z</b>	25	6	-	0.70	178	23,000	0.45	¼	¾	0.4
<b>TG-38ZL</b>	25	6	-	0.63	163	23,000	0.50	¼	¾	-
<b>TSG-3C</b>	38	6	-	1.60	340	12,700	0.80	¼	¾	0.7
<b>TSG-3CL</b>	38	6	-	1.67	402	12,700	0.50	¾	¾	0.7
<b>TSG-3F/3L</b>	75 x 13 x 9.5	-	3,000	1.6 / 1.78	305 / 367	12,700	0.80 / 0.50	¼ / ¾	¾	0.7
<b>TSG-5L/5S</b>	125 x 19 x 12.7	-	3,000	3.03 / 3.0	457 / 400	7,600	0.60 / 1.10	¾	½	1.4
<b>TSG-6L/6S</b>	150 x 25 x 15.9	-	3,000	4.2	430	6,000 / 6,300	1.20	¾	½	2.1